


SAFE ENTRY KIOSK

WITH TEMPERATURE TAKING & AUTOMATIC HAND SANITIZER

21.5" Android Terminal

Automate the process of checking in your visitors or customers, with this all-in-one self-service kiosk. In just 30 seconds, they can sanitise their hands, scan their ID's barcode or the TraceTogether token's QR code for SafeEntry, and get their temperature taken seamlessly. And with the additional LCD screen, upsell to your customers with advertisements. Perfect for all public areas such as buildings, shopping malls, schools, etc.




Hands Free Operation



TraceTogether QR Code



SafeEntry ID Barcode



Temperature Taking



21.5" Android Terminal



Automatic Hand Sanitiser



Video & Image Advertisements



Ethernet & WIFI

ITEM	SPECIFICATION	
Input	AC 100-240V ~ 50/60Hz 2A	
Water/Dust Proof	IP protection level certification	
CPU	ARM Cortex A53 Dual Core, 64bit, 1.2Ghz	
Chipset	Hi3751 V310	
GPU	Mali-450 Quad-Core 3D GPU (supports OpenGL ES 2.0/1.1/1.0 OpenVG 1.1)	
RAM	1GB DDR3 as standard	
Storage	8GB	
OS	Android 4.4.2	
Display	21.5" TFT LCD, 1920 x 1080p, LVDS	
Video Input	Format	480i, 576i
	Video System	PAL / NTSC / SECAM
	Video Level	1.0 V _{p-p} +/- 5%
	HDMI	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 4K2K
	UART	TTL
	USB	MPEG 1.2, H.264, VC-1, MPEG-4 up to FHD
TF-Card	(1920 x 1080), RM/RMVB up to 720P	
Audio Input	CVBS Audio (L/R RCA input, 0.2~2.0 V _{RMS})	

ITEM	SPECIFICATION	
Audio Decode	Dolby Digital, Dolby Digital PLus, Dolby TrueHD, DTS, DTS-HD, MPEG L1/L2, MP3, AAC, LC, HE, AACV2, LPCM APE, FLAC, OggVorbis, ARM-NB, G.711(u/a)	
Video Output	CVBS (format: 480i, 576i; video level: 1.0V _{p-p} +/-5%)	
Audio Output	CVBS Audio	L/R RCA Output (250mV _{RMS} +/- 10%)
	Frequency Response	10Hz ~ 15KHz @ +/-3dB 0dB reference signal at 1KHz)
	Max Output Power	2 x 8W (8ohm) THD+N < 10% @1KHz
Power	DC 12V (DC Input)	
	3.3V / 5V / 12V (to panel)	
	Standby Power Consumption < 0.5W	
Connection	WIFI	802.11 b/g/n, built-in module optional, need ANT
	Ethernet	10/100M auto-identification and DHCP, USB driver
COMB Filter	3D	
Deinterlace	3D	
Work Temp.	-10 ~ 55°C	
Storage Temp.	-10 ~ 60°C	

Transportation Enviroment

Temperature -20 ~ 60°C, Humidity 5% ~ 85%RH
Vibration test - IEC60721-3-2 Class 2M2

Environment

Operating Environment:
temperature 0 ~ 40°C, humidity 35% ~ 85% RH, no condensation
Storage Environment:
temperature 0 ~ 40°C, humidity 35% ~ 85% RH, no condensation

Weight

Gross weight: 18.5KG

Package Size

Dimension: 1160 x 290 x 470mm

Certification & Standard

Certification: CCC / CB / CE
Static electricity level:
According to contact discharge: level 2
Comply with air discharge: level 3

Parts in package



AC Power Cord



Manual/Guarantee Card

